Detailed Specification & Technical Data





244585-C5E

24-Port Category 5e Screened Patch Panc.

PRODUCT OVERVIEW	-
Product Description	24-Port Category 5e Screened Patch Panel, T568A/B Wiring, 1.75" High
Product Overview	The Category 5e Screened Patch Panel is available in a 24-port version and provides the ability to terminate fully screened category 5e cable. Th s panel exceeds ANSI/TIA-568-C.2 specifi ations for superior performance. The panel features front labeling areas and comes with a rear cable management bar that mounts easily to the back of the panel.
Package Qty.	1

SPECIFICATIONS & DIMENSIONS	-
Transmission Performance	ANSI/TIA-568-C.2: meets or exceeds category 5E (1-250 MHz) component specifi ations
Jack Type	8p8c (8-position, 8-contact) "RJ45" style
Mounting Dimensions	19" rack mountable, 1.75" (1 RMU) high
Environmental Characteristics	Storage: -40 °C - +70 °C (-40 °F - +158 °F) Operation: -10 °C - +60 °C (+14 °F - +140 °F) RH (operation): max non-condensing 93 %
Warranty	5-year limited component warranty 10-year Signamax Link/Channel Warranty 15-year Signamax Extended Component Warranty 25-year Signamax Cabling System Warranty
Media Type	Category 5E F/UTP