

Detailed Specification & Technical Data



FI-4242

BRILLIANCE LC OM3 50/125



| | |
|-------------------------|--|
| PRODUCT OVERVIEW | - |
| Product Description | BRILLIANCE LC OM3 50/125 LASER OPTIMIZED |
| Product Overview | FX Brilliance Universal LC Field Installable Connector, Multimode, OM3-OM4, Aqua Housing, 1/Pack, with support for 250 um (using Breakout kit), 900 um, 2 mm and 3 mm fiber (using jacketed boots). Includes 900 um boot, other accessories (Breakout Kit & jacketed boots) sold separately. |
| Package Qty. | 1 |

| | |
|-------------------------|-----------|
| PRODUCT FEATURES | - |
| Color | AQUA - AQ |

| | |
|--|---|
| SPECIFICATIONS & DIMENSIONS | - |
| Technical Information | 1.12lb Tensile Strength |
| Transmission Performance | Max Insertion Loss: .5dB Typical Insertion Loss: .2dB Return Loss: 25dB |
| Connectors | LC |
| Applicable Standards | TIA/EIA-604-10A (FOCIS 10) TIA 568-C.3 |
| Physical Characteristics | 1.496" Length x .244" Width x .43" Height - .208lbs Weight |
| Environmental Characteristics | -40deg - +75 deg C - Operating Temperature |
| Media Type | 50/125 OM3 - MultiMode Fiber Optic |