

# Detailed Specification & Technical Data

## SGKF-cc-xx-10

Standard Keystone Wall Plates

<b>Overview</b>	
<b>Overview</b>	
Single-gang faceplates are available in 1-, 2-, 3-, 4-, port versions and allow for mounting any combination of keystone jacks and multimedia modules.	
<b>Key Features</b>	
High-impact thermoplastic, UL94V-0 fire-retardant	
W: 70 mm (2.75 in), H: 114 mm (4.5 in), screw spacing: 83 mm (3.28 in)	
Five color options	
<b>Specifications</b>	
<b>CONSTRUCTION</b>	
High impact thermoplastic, UL94V-0 fire retardant	
<b>OVERALL DIMENSIONS</b>	
W: 69.9 mm H: 114.3 mm	
W: 2.75 in H: 4.50 in	
<b>MOUNTING DIMENSIONS</b>	
Mounting screw holes distance: 83.3 mm (3.28 in)	
<b>KEYSTONE MODULE MOUNTING DIMENSIONS</b>	
Standard keystone footprint	
Panel opening: 14.7 mm (0.579 in) × 19.30 mm (0.760 in)	
<b>OPERATING TEMPERATURE</b>	
-10 °C to +60 °C (-14 °F to +140 °F)	
<b>Part Numbers Structure</b>	
SGKF-xx-cc-10	
xx: Number Of Ports (1, 2, 3, or 4)	
cc: Color: Light Ivory (IV), White (WH)	
10 - Number of Units / Pack	

