



C6CS-314GY-xxFB

Category 6 F/UTP Assembly

PRODUCT OVERVIEW	-
Product Description	Category 6 Screened Patch Cords w/Snag-Proof Boots
Product Overview	<p>West Penn continues to set the standard for high-quality, high-performance patch cords with two series of category 6 patch cords. Our category 6 cords are 100% transmission tested to component performance as specified in ANSI/TIA-568-C.2. Assembled in a controlled environment using advanced manufacturing techniques to ensure consistent quality, these patch cords provide exceptional performance when mated with our category 6 screened connecting hardware.</p> <p>West Penn category 6 screened patch cords incorporate slim-profile snag-free boots, which protect the plug latch, and a flexible, but durable cable strain relief and are compatible with both T568A and T568B wiring schemes. Category 6 screened patch cords are manufactured using ETL-verified stranded cable designed for greater flexibility and service life and are available in a variety of standard lengths.</p>
Package Qty.	1

PRODUCT FEATURES	-
Features	<ul style="list-style-type: none"> • Transmission performance exceeds TIA/EIA-568-C.2 component performance specifications • 100% factory transmission tested • ScTP (FTP) construction protects against most EMI sources • Single shielded ETL verified 26 AWG stranded cable • Rated for at least 750 plug insertions • Enhanced plug-to-jack connection integrity • T568A/B wiring scheme compatible • Slim-profile snag-free boots • Durable flexible cable strain relief

SPECIFICATIONS & DIMENSIONS	-
Transmission Performance	ANSI/TIA/EIA-568-C.2: exceeds category 6 (1-250 MHz) specifications ISO/IEC 11801 2nd Ed.: exceeds category 6 (1-250 MHz) specifications
Cordage	Jacket diameter: < 6.35 mm (0.25 in) Construction: 4 pairs, 7 strands 26 AWG, UTP, high density polyethylene insulation, overall metal foil screen fire retardant PVC compound jacket
Wiring Scheme	ANSI/TIA/EIA-568-C.2: T568A & T568B ISO/IEC 11801 2nd Ed.: 8-position conductor/pair assignment (1-2/3-6/4-5/7-8)
Physical Characteristics	Retention: 50 N (11 lbf) for 60±5 s Mating cycle life: min 750 cycles Tensile strength: ≥ 20 N per wire
Electrical/Optical Characteristics	Insulation resistance: min 500 MOhm @ 100 Vdc Dielectric withstanding voltage: 1,000 Vdc/ac peak contact to contact @ 60 Hz for 1 min Contact resistance: max 20 Mohm
Environmental Characteristics	Storage: -40 °C-+70 °C (-40 °F-+158 °F) Operation: -10 °C-+60 °C (+14 °F-+140 °F) RH (operation): max non-condensing 93 %
Warranty	5-year limited component warranty 10-year Signamax Link/Channel Warranty 15-year Signamax Extended Component Warranty 25-year Signamax Cabling System Warranty

PRODUCT PARTS	-
C6CS-314GY-xxFB	Replace cc: Color GY Gray Replace xx: 3,7,10,15,20,25 ft